

CITGO SYNTHETIC GEAR LUBRICANTS



Date 10/06

- DESCRIPTION:** CITGO Synthetic Gear Lubricants are heavy-duty, synthetic gear and bearing lubricants designed for use in manual transmissions, transfer cases and differentials of passenger cars, trucks, farm tractors, construction and miscellaneous other industrial equipment. Blended from high viscosity index, low pour point synthetic base stocks, these oils provide maximum protection to gears and bearings operating over a wide range of temperatures, speeds and loads. Their superb resistance to oxidation provides the benefit of extended drain intervals. Available in three viscosity grades: SAE 75W-90, 80W-140 and 50.
- PROPERTIES:**
- Superior oxidation resistance for extended drain intervals.
 - Excellent load carrying properties (SAE 75W-90 and 80W-140) for maximum protection against component wear.
 - High viscosity index and low pour point synthetic base stocks provide reduced fluid friction with resultant fuel savings potential during low temperature start-up or operating conditions.
 - Excellent demulsibility – separates water readily.
 - Shear resistant.
 - Provides full protection to system parts against rust and corrosion.
 - Non-foaming.
- APPLICATIONS:** CITGO Synthetic Gear Lubricants (SAE 75W-90 and 80W-140) are recommended for differentials, manual transmissions for which hypoid-type lubricants are required and transfer cases for heavy equipment – trucks, tractors, industrial gear drives, automobiles, farm machinery, etc. These products meet or exceed the following performance requirements:
- API Service Classification GL-5 and MT-1
 - SAE J2360
 - U.S. Military Specification MIL-L-2105D and MIL-PRF-2105E
 - Scania STO 1:0
 - Eaton Roadranger E500/Shaes 256
 - Mack GO-J Plus (75W-90)
 - Mack GO-J (80W-140)
 - ArvinMeritor O-76N
 - International TMS-6816
 - General Electric D 50E9C
 - Harnishfeger (P&H) 474
- CITGO Synthetic Gear Lubricant SAE 50 is recommended for heavy-duty service in manual transmission for which the manufacturer normally recommends either engine oils or GL-1 to GL-4 lubricants. This product contains antiwear, rust, oxidation, foam and corrosion inhibitors to protect bearings and synchronizers and to promote longer transmission life. As in the other products in this series, CITGO Synthetic Gear Lubricant SAE 50 provides improved start-up, easier shifting and less gear wear in low temperature environments. Less friction, less drag and improved oxidation resistance combine to provide fuel economy benefits and longer drain intervals.

This product meets or exceeds the following performance requirements:

- API GL-4, MT-1
- MAN 341 SL
- Eaton Roadranger Extended Drain (E500) PS-164 Rev. 7, PS 164/O81 (Approved for 500,000 miles drain intervals)
- Mack TO-A 500,000 Mile Extended Drain
- ArvinMeritor Extended Drain O-81 500,000 Mile Extended Drain
- Rockwell International 0-80 (former)
- Meritor ZF Freedom Line ZF TE-ML-04D
- Volvo STD 97305
- International TMS 6816 500,000 Mile Extended Drain
- ZF AS-Tronic

TYPICAL PROPERTIES:

CITGO SYNTHETIC GEAR LUBRICANTS

SAE GRADE	75W-90	80W-140	50
Material Code	631809001	631814001	631815001
API Classification	GL-5	GL-5	GL-4
AGMA Grade	4	5-6	4
Gravity, ASTM D 4052, °API	33.4	31.5	33.1
Pounds Per Gallon	7.14	7.23	7.16
Flash Point, ASTM D 92, °F (°C)	405 (204)	410 (210)	435 (224)
Pour Point, ASTM D 97, °F (°C)	-65 (-54)	-54 (-48)	-49 (-45)
Color, ASTM D 1500	1.5	1.5	2.0
Viscosity, ASTM D 445, cSt at 40°C	111	273	128
cSt at 100°C	15.1	29.1	17.6
Viscosity Index	143	142	151
Brookfield Viscosity, ASTM D 2270			
cP at -18°C	5,715	22,700	6,835
cP at -26°C	-	60,950	-
cP at -40°C	93,050	-	<120,000
Foam Test, ASTM D 892	Pass	Pass	Pass
Copper Corrosion, ASTM D 130	1A	1A	1A
Rust Protection, ASTM D A/B	Pass	Pass	Pass