



El Mar® Mid Ash Heavy Duty

Conoco® El Mar Mid Ash Heavy Duty is a high-quality, mid-ash, dispersant-detergent gas engine oil designed for use in naturally aspirated and moderately to highly turbocharged 4-stroke cycle natural gas engines. It is particularly recommended for use in natural gas engines and dual-fuel engines burning sour gas or landfill gas.

El Mar Mid Ash Heavy Duty is formulated with field-proven performance additives to provide excellent resistance to oxidation and nitration, protect against piston scuffing and wear, and minimize the formation of sludge and piston deposits for good engine cleanliness. It has a high alkaline reserve (TBN) to protect engines operating under corrosive conditions, such as when burning sour gas, digester gas or landfill gas.

Applications

- 4-stroke cycle gas and dual-fuel engines burning sour gas or landfill gas
- 4-stroke cycle natural gas engines in wastewater treatment plants fueled by digester gas
- 4-stroke cycle converted irrigation engines running on natural gas or LPG
- Other 4-stroke cycle natural gas engines where the manufacturer specifies a mid-ash gas engine oil

El Mar Mid Ash Heavy Duty is recommended for use in natural gas engines manufactured by:

- Cooper Superior
- Waukesha (VHP GL turbocharged lean-burn engines, models 3521, 5115, 7042, 9390)

Features/Benefits

- Excellent resistance to oxidation and nitration
- High alkaline reserve to combat acidic combustion by-products when burning sour gas
- High dispersancy protects against sludge and varnish formation
- Protects against scuffing and wear
- Protects against rust and corrosion
- Excellent low-temperature performance

**Mid-Ash
Natural Gas
Engine Oil**

**U.S. Technical
Services Hot Line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**E-mail address:
*conocolubricants@
conocophillips.com***

<http://lubes.conoco.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Does not contain any bright stock, which can cause harmful carbon deposits

El Mar® Mid Ash Heavy Duty

Typical Properties

SAE Grade	30	40	15W-40
Specific Gravity @ 60°F	0.879	0.883	0.877
Density, lbs/gal @ 60°F	7.33	7.36	7.31
Color, ASTM D1500	3.5	3.5	3.0
Flash Point (COC), °C (°F)	234 (453)	254 (489)	232 (450)
Pour Point, °C (°F)	-36 (-33)	-27 (-17)	-45 (-49)
Viscosity, Kinematic			
cSt @ 40°C	87.4	140	114
cSt @ 100°C	11.2	15.2	14.8
Viscosity Index	110	105	138
Cold Cranking Viscosity, cP	—	—	6,300
@ (°C)	—	—	(-20)
Sulfated Ash, ASTM D874, wt %	1.0	1.0	1.0
Total Base Number (TBN), ASTM D2896	7.9	7.9	7.9
Phosphorus, wt %	0.097	0.097	0.097
Zinc, wt %	0.109	0.109	0.109

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, and the Conoco logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.