

December 3, 2007

P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current as of December 3, 2007.

SYNTHETIC CHAIN LUBRICANTS

DSL[®]-10 Chain Oil

Summit DSL[®]-10 chain oil is a unique blend of diester base stocks and an additive system designed to meet the demanding requirements for a low viscosity, thermally stable chain oil. This blend provides for the following benefits to chains:

1. *Excellent anti-wear properties to prolong chain life*
2. *Light viscosity for spraying the lubricant onto the chain*
3. *High temperature capabilities*
4. *Cleaning of the chain as it operates*
5. *Anti-oxidants to reduce gumming and thickening*
6. *Water insoluble*
7. *Penetration*

Summit DSL[®]-10 is also suitable for general purpose high temperature applications requiring a low viscosity lubricant.

Physical Properties

Characteristic	Typical Performance
Viscosity	
@ 40°C, cSt	10.9
@ 100°C, cSt	3.16
@ 100°F, SUS	64.5
@ 210°F, SUS	36.9
Viscosity Index	166
Flash Point, °F (°C)	320 (160)
Fire Point, °F (°C)	356 (180)
Pour Point, °F (°C)	-76 (-60)

