

June 21, 2007

P.O. Box 131359 • Tyler, CR 2120, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet



NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current as of June 21, 2007.

SYNTHETIC VACUUM PUMPS

SHV SERIES

The *Summit SHV Series* is formulated from vacuum distilled ultra-pure synthetic hydrocarbon base stock to provide an extremely low vapor pressure vacuum pump lubricant. These non-foaming fluids have excellent water separation and provide protection against wear, rust and corrosion. The SHV Series is an extended life lubricant designed to function in applications subject to severe temperature and environmental conditions.

Physical Properties

PRODUCTS	SHV-15	SHV-22	SHV-32	SHV-68	SHV-100
ISO Grade	15	22	32	68	100
Viscosity					
@ 40°C, cSt	15.2	21.2	29.9	63.7	93.0
@ 100°C, cSt	3.54	4.51	5.70	9.60	12.5
@ 100°F, SUS	83.2	110	154	327	482
@ 210°F, SUS	38.2	41.4	45.3	58.7	69.8
Viscosity Index	113	129	134	132	130
Pour Point, °F	-70	-80	-80	-55	-44
(°C)	(-57)	(-62)	(-62)	(-48)	(-42)
Flash Point, °F	415	430	450	500	510
(°C)	(213)	(221)	(232)	(260)	(266)
Autoignition Point °F	710	720	730	745	760
(°C)	(377)	(382)	(382)	(396)	(404)
Copper Strip Corrosion	1A	1A	1A	1A	1A
Emulsion Tendency	40/40/0 (10 mins.)	40/40/0 (10 mins.)	40/40/0 (10 mins.)	40/40/0 (10 mins.)	40/39/0 (15 mins.)
Vapor Pressure, mm Hg. (Modified ARS 184-R1)					
100°F	<0.00047	<0.00040	<0.00030	<0.00010	<0.00004
200°F	<0.00101	<0.00080	<0.00062	<0.00050	<0.00018
300°F	<0.00190	<0.00170	<0.00160	<0.00130	<0.00085

The Summit SHV Series are compatible with commonly used seal and gasket materials in vacuum pump service.