

May 13, 2002

P.O. Box 131359 • Tyler, Texas 75713, Phone 903.534.8021 • Fax 903.581.4376

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current as of May 13, 2002.

SYNTHETIC AIR COMPRESSOR

ULTIMA

Summit Ultima is a high performance lubricant formulated specifically to outperform other synthetic rotary compressor lubricants on the market. Ultima employs a unique base stock that allows improvements in oxidation resistance and sludge and deposit formation over conventional synthetic base stocks. It is also compatible with existing O.E.M. provided lubricants. Please contact your Summit representative for additional information.

Physical Properties

PRODUCTS	Ultima	Ultima 68
ISO Grade	46	68
Viscosity		
@ 40°C, cSt	48.7	64.2
@ 100°C, cSt	7.86	9.45
@ 100°F, SUS	249	329
@ 210°F, SUS	52.6	58.1
Viscosity Index	130	127
Specific Gravity	0.910	0.914
Flash Point, °F (°C)	475 (246)	450 (232)
Pour Point, °F (°C)	-55 (-48)	-50 (-46)
RBOT, Minutes	3038	3100