

# Material Safety Data Sheet



Product Name: **SUMTECH SG 460**  
Date: September 29, 2004  
Printed: 09/29/04  
Replaces: May 27, 2004  
Page: 1 Of 4

---

## Section 1 – Product and Company Identification

Company: Summit Industrial Products, Inc.  
9010 County Road 2120  
Tyler, Texas 75707  
Phone: (903) 534-8021  
Fax: (903) 581-4376  
Emergency Telephone# 1-800-424-9300 (Chemtreec)

Product Name: Sumtech 460  
Product Use: Lubricating Paste

---

## Section 2 – OSHA Hazardous Ingredients

<b>Ingredient</b>	<b>TLV</b>	<b>PEL</b>
Synthetic Hydrocarbon Oil	N/Ap	N/Ap
Lithium Soap Thickener	N/Ap	N/Ap
Mineral Oil	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>
Zinc Compound	N/Ap	N/Ap

---

## Section 3 Hazards Identification

**Eye Contact:** May cause mild irritation upon immediate contact.

**Skin contact:** Prolonged or repeated contact may cause the removal of skin oils, possibly leading to irritation or dermatitis.

**Inhalation:** Vapor inhalation under ambient conditions will not occur. The inhalation of vapors (generated at extremely high temperature only) or mist may cause a mild irritation of the mucous membranes of the upper respiratory tract. Harmful concentrations of mists and/or vapors are unlikely to occur through reasonable and customary use of this product.

**Ingestion:** No acute or chronic effects expected. However, minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury.

---

## Section 4 Emergency and First Aid Procedures

**After contact with eyes:** Flush eyes with plenty of water for 15 minutes. If irritation persists, or if an infection develops, seek medical attention.

**After contact with skin:** Wash off with soap and plenty of water. Apply skin cream if necessary. Seek medical attention if irritation or infection occurs. Remove contaminated clothing and wash before reuse.

**After inhalation:** If overcome by product vapor heated to extreme temperatures, immediately move from exposure and get medical attention. If breathing is irregular, start resuscitation or administer oxygen if available. If overexposed to mist, remove from further exposure until excessive mist condition subsides.

**After ingestion:** If large amounts are swallowed, do not induce vomiting. Get medical attention.

**Advice to doctor:** Treat symptomatically.

**After ingestion:** Do not induce vomiting. Get medical attention

---

The information herein is given in good faith, but without warranty, express or implied. All risks of use of the product are therefore assumed by the user. Appropriate warnings and safe handling procedures must be provided to handlers and users.

# Material Safety Data Sheet

Product Name: **SUMTECH SG 460**  
Date: September 29, 2004  
Printed: 09/29/04  
Replaces: May 27, 2004  
Page: 2 Of 4

---



## Section 5 Exposure Controls

**Eye protection:** Wear safety goggles if splashes may occur. Do not wear contact lenses when using chemicals.

**Hand protection:** Wear chemical resistant gloves

**Body protection:** Wear clean, body-covering clothing to minimize dermal exposure.

**Ventilation:** Under normal conditions of use, no special ventilation is required; however, if vaporized or misted, use local exhaust if possible.

**Respiratory protection:** No special respiratory protection is required. However, if product is overheated beyond conditions of normal use, or misted, wear the appropriate NIOSH-approved respiratory protection.

**Other protection measures:** Safety showers, eye wash fountains, and washing facilities should be readily available.

---

## Section 6 – Fire Fighting Measures

**Flash point:** N/Av Method: ASTM D 92

**Lower explosion limit:** N/Av

**Upper explosion limit:** N/Av

**Extinguishing media:** Water spray, foam, dry powder, carbon dioxide (CO<sub>2</sub>)

**Unusual fire and explosion hazards:** Empty metal containers retain product residue. Do not pressurize, cut, weld, drill, solder or expose container to heat, flame, sparks, or other sources of ignition: it may explode, causing serious injury or death. Exposure to heat builds up pressure in container. Cool with water spray.

**Special fire Fighting Procedures:** If leak or spill has not ignited, use water spray to disperse any vapor and to flush spills away from ignition sources. Use self-contained breathing apparatus for enclosed or confined spaces or as otherwise needed. Do not use direct stream of water, material may float and re-ignite.

---

## Section 7 – Accidental Release Measures

If product leaks or is inadvertently spilled, eliminate ignition sources and isolate surrounding spill area with the proper containment system to prevent the spill from reaching waterways. Add absorbent and soak up the product. Collect product and absorbent, place in a chemical waste container for proper disposal.

---

## Section 8 – Handling and Storage

Avoid contact with skin and remove soiled or soaked clothing. Wash hands with soap and water before eating drinking and/or smoking. Clean skin thoroughly after work and if necessary, apply skin cream.

Store product under normal temperature and pressure.

Store product away from heat sources and food products.

---

The information herein is given in good faith, but without warranty, express or implied. All risks of use of the product are therefore assumed by the user. Appropriate warnings and safe handling procedures must be provided to handlers and users.

# Material Safety Data Sheet



Product Name: **SUMTECH SG 460**  
Date: September 29, 2004  
Printed: 09/29/04  
Replaces: May 27, 2004  
Page: 3 Of 4

---

## Section 9 Physical and Chemical Properties

**Boiling Point:** N/Av  
**Pour Point:** N/Av  
**Vapor Pressure (mm Hg.):** N/Av  
**Vapor Density (Air = 1):** N/Av  
**Solubility in Water:** Insoluble  
**Specific gravity (H<sub>2</sub>O = 1):** 0.89  
**Evaporation rate (ether = 1):** N/Av  
**Appearance and odor:** Yellowish paste with a neutral odor.

---

## Section 10 Stability and Reactivity

**Stability:** Stable  
**Conditions to avoid:** Open flames and other sources of heat  
**Materials to avoid:** Strong oxidizing agents such as pure oxygen  
**Hazardous decomposition products:** Fumes, smoke, carbon monoxide and carbon dioxide.  
**Hazardous polymerization:** Will not occur.

---

## Section 11 – Toxicological Information

Acute toxicity: N/Av for this product.  
Chronic toxicity: N/Av for this product.

---

## Section 12 – Disposal Considerations

Under RCRA, it is the user's responsibility to determine, at the time of disposal, whether the product meets any of the criteria for a hazardous waste defined in 40 CFR 261 Subpart C.

---

## Section 13 Transportation Information

Proper Shipping Name	Hazard Class or Division	UN ID	Packing Group
N/Av			

---

The information herein is given in good faith, but without warranty, express or implied. All risks of use of the product are therefore assumed by the user. Appropriate warnings and safe handling procedures must be provided to handlers and users.

# Material Safety Data Sheet

Product Name: **SUMTECH SG 460**  
Date: September 29, 2004  
Printed: 09/29/04  
Replaces: May 27, 2004  
Page: 4 Of 4

---



---

## Section 14 Regulatory Information

All product components comply with all applicable rules and orders under the Toxic Substance Control Act (TSCA).  
The Zinc Compound (~1) in this product is a SARA Title III Section 313 chemical.

---

## Section 15 Additional Information

HMIS Rating: Health -1 Flammability - 1 Reactivity - 0 Personal Protection - B

Unk. = Unknown N/Ap = Not Applicable N/Av = Not Available ~ = Approximately

---

The information herein is given in good faith, but without warranty, express or implied. All risks of use of the product are therefore assumed by the user. Appropriate warnings and safe handling procedures must be provided to handlers and users.