



CITGO RUST-O-LENE® OIL 10

Date 1/09

DESCRIPTION: CITGO RUST-O-LENE 10 is a MIL-L-2104(B) quality engine (SAE 10) oil designed to provide temporary rust protection for engines during shipment and storage, and as a general rust preventative and circulating oil.

QUALITIES: CITGO RUST-O-LENE 10 is formulated from high VI base stocks, an effective rust inhibitor, an anti-wear/scuffing agent, and has some sludge and varnish protection.
CITGO RUST-O-LENE 10 will displace water from metal surfaces.

APPLICATIONS: CITGO RUST-O-LENE 10 is suitable for rust protection of engine blocks and assembled engines during shipment and storage.
CITGO RUST-O-LENE 10 can be used in hydraulic and circulating oil systems for industrial equipment requiring better protection from rust.
CITGO RUST-O-LENE 10 is used as a general oil based lubricant for applications requiring MIL-L-21260 Humidity Cabinet protection of 300 hours or more.

TYPICAL PROPERTIES:

CITGO RUST-O-LENE® OIL 10

ISO Vis Grade (SAE Grade)	35 (10)
Material Code	637145001
Gravity, ASTM D 4052, °API	30.7
Flash Point, ASTM D 92, °F (°C)	395 (202)
Viscosity, ASTM D 445, cSt, at 40°C	35.0
ASTM, D 2161, SUS, at 100°F	180
Pour Point, ASTM D 97, °F (°C)	-20 (-29)
Color, ASTM D 1500	1.5
Rust Protection, Humidity Cabinet, ASTM D 1748, hrs	300