



Wireline

Wireline is a high-quality, tacky, viscous, high viscosity index lubricant specifically developed for lubrication and sealing of braided wirelines and cables used in oil and gas wells for cased-hole logging, pipe recovery service, tubing conveyed perforating, production logging and reservoir analysis.

Wireline is applied in once-through operation. It maintains a seal around the moving wireline in high-pressure environments to prevent the escape of wellbore corrosive fluids and gases between the wireline outer diameter and the flow tube inner diameter. It provides excellent protection against corrosion, including saltwater corrosion, as well as rust preventive properties for storage of logging cables. It also has excellent low-temperature fluidity to prevent wireline seizure and breakage in cold weather.

Applications

- Braided wirelines and cables used in oil & gas wells
- Cased-hole logging operations
- Pipe recovery service
- Tubing-conveyed perforating
- Production logging
- Reservoir analysis

Note: This product is *not* designed for and should not be used in wire rope applications.

Features/Benefits

- Clear color
- Easy to apply in warm and cold weather
- Tacky; stays put and does not drip
- Excellent corrosion protection
- Excellent low-temperature fluidity
- High viscosity index
- Easily pumpable in wireline injection units

**High-Quality
Wireline Lubricant
& Sealant**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-877-445-9198**

**International
Customer Service:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**



Wireline

Typical Properties

ISO Grade	68	220	460	680
Specific Gravity @ 60°F	0.865	0.863	0.862	0.860
Density, lbs/gal @ 60°F	7.21	7.19	7.17	7.16
Color, ASTM D1500	L 0.5	L 0.5	L 0.5	L 0.5
Flash Point (COC), °C (°F)	225 (437)	225 (437)	225 (437)	225 (437)
Pour Point, °C (°F)	-39 (-38)	-39 (-38)	-36 (-33)	-36 (-33)
Viscosity,				
cSt @ 40°C	68.0	220	460	680
cSt @ 100°C	10	28	55	76
Rust Test, ASTM D665 B	Pass	Pass	Pass	Pass

ISO Grade	1500	5000	7500	10000
Specific Gravity @ 60°F	0.859	0.855	0.854	0.852
Density, lbs/gal @ 60°F	7.15	7.12	7.11	7.10
Color, ASTM D1500	L 0.5	L 0.5	L 0.5	L 0.5
Flash Point (COC), °C (°F)	225 (437)	225 (437)	225 (437)	225 (437)
Pour Point, °C (°F)	-33 (-27)	-30 (-22)	-27 (-17)	-24 (-11)
Viscosity,				
cSt @ 40°C	1,500	5,000	7,500	10,000
cSt @ 100°C	150	460	680	1,000
Rust Test, ASTM D665 B	Pass	Pass	Pass	Pass

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2011 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.