



## Syndustrial® R&O Oil

Syndustrial R&O Oil is a premium quality, synthetic diester lubricant developed for use in air compressors and select steam turbines operating under severe-service conditions, and in moisture-free environments. It is particularly recommended for use in applications where operating conditions may be unfavorable or too severe for conventional mineral oil-based lubricants.

Syndustrial R&O Oil is formulated to provide long service life and excellent performance over a wide temperature range. It has excellent oxidation resistance and thermal stability at high temperatures to minimize sludge and varnish formation, and provide long service life. It also has excellent low-temperature properties for use over a wide temperature range. It has good natural detergency to help minimize deposit formation in air compressors and on the bearing surfaces of steam turbines. It protects system components against rust, corrosion and wear. It has good water-separating properties and is resistant to excessive foam buildup. It has lower volatility than conventional mineral oil-based lubricants for reduced oil consumption.

### Applications

- Reciprocating air compressors<sup>(1)</sup>
- Select rotary air compressors operating in a dry environment<sup>(1)</sup>
- Elliott ring-oiled turbines, where a synthetic diester turbine oil is specified
- Circulating systems requiring a synthetic diester lubricant
- Steam turbines where the manufacturer specifies a synthetic diester lubricant
- Plain and rolling-element bearings operating at very high or very low temperatures
- Industrial equipment operating over a wide temperature range where an inhibited mineral oil is recommended<sup>(2)</sup>

<sup>(1)</sup> **Note:** Always follow the equipment manufacturer's recommendations regarding the use of diester lubricants and selection of proper viscosity grade. Typically, rotary air compressors and turbines require an ISO 32 or ISO 68 viscosity grade, and reciprocating compressors require an ISO 100 or ISO 150 viscosity grade.

<sup>(2)</sup> **Note:** Syndustrial R&O Oil is **not** compatible with mineral oil-based lubricants. Mixing should be avoided to ensure optimum performance.

**Synthetic Diester  
Lubricant For  
Air Compressors &  
Some Turbines;  
Rust & Oxidation  
Inhibited**

### Contact Information

**U.S. Customer  
Service:  
1-800-822-6457**

**Technical Hot Line:  
1-877-445-9198**

**International  
Customer Service:  
+1-832-486-3363**

**E-mail address:  
lubricants@  
conocophillips.com**



### **Features/Benefits**

- Excellent resistance to thermal breakdown at high temperatures
- Excellent oxidation resistance to minimize sludge and varnish formation
- Protects against wear
- Protects against rust and corrosion
- Natural detergency
- Excellent low-temperature properties
- Extended service intervals compared with conventional mineral oil-based lubricants

**Note:** For information on compatibility with seals, paints and plastics, please call our Technical Support Hot Line.

---

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

---

Copyright © 2011 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.



## Syndustrial® R&O Oil

### Typical Properties

| ISO Grade                                  | 32        | 68        | 100       | 150       |
|--|-----------|-----------|-----------|-----------|
| Specific Gravity @ 60°F                    | 0.941     | 0.965     | 0.961     | 0.957     |
| Density, lbs/gal @ 60°F                    | 7.84      | 8.04      | 8.00      | 7.97      |
| Color, ASTM D1500                          | 0.5       | 0.5       | 0.5       | 0.5       |
| Flash Point (COC), °C (°F)                 | 243 (469) | 254 (489) | 260 (500) | 265 (509) |
| Pour Point, °C (°F)                        | -51 (-60) | -42 (-44) | -39 (-38) | -39 (-38) |
| Viscosity,                                 |           |           |           |           |
| cSt @ 40°C                                 | 31.0      | 65.0      | 98.5      | 150       |
| cSt @ 100°C                                | 5.0       | 8.4       | 10.9      | 15.1      |
| SUS @ 100°F                                | 161       | 337       | 515       | 786       |
| SUS @ 210°F                                | 43.0      | 54.5      | 63.5      | 80.1      |
| Viscosity Index                            | 74        | 94        | 94        | 101       |
| Acid Number, ASTM D974, mg KOH/g           | 0.39      | 0.39      | 0.39      | 0.39      |
| Copper Corrosion, ASTM D130                | 1a        | 1a        | 1a        | 1a        |
| Demulsibility, ASTM D1401, minutes to pass | 10        | 10        | 15        | 15        |
| Foam Test, ASTM D892                       | Pass      | Pass      | Pass      | Pass      |
| Four-Ball Wear, ASTM D4172,                |           |           |           |           |
| Scar Diameter, mm                          | 0.70      | 0.80      | 0.70      | 0.66      |
| FZG Scuffing Test, ASTM D5182,             |           |           |           |           |
| Failure Load Stage                         | 9         | 9         | 9         | 9         |
| Oxidation Stability, RPVOT,                |           |           |           |           |
| ASTM D2272, minutes                        | >1,750    | >1,750    | >1,750    | >1,750    |
| Rust Test, ASTM D665 A&B                   | Pass      | Pass      | Pass      | Pass      |

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2011 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.