



Ecoterra® Rock Drill Fluid

Conoco® Ecoterra Rock Drill Fluid is a high-quality, adhesive, extreme-pressure (EP) lubricant specially developed for the lubrication of percussion rock drills used in surface and underground mining operations. It also is recommended for other air-powered tools such as jackhammers, pavement breakers and drifters. It is formulated with an ashless, chlorine-free additive package for reduced environmental impact.

Ecoterra Rock Drill Fluid is specially formulated with select non-chlorinated additives to provide excellent protection for pneumatic percussion tools. It has high load-carrying capacity to protect against wear and seizure of sliding metal surfaces under heavy or shock-load conditions. It has good adhesiveness to metal surfaces in the presence of moisture, and contains inhibitors to protect against rust and corrosion. It has good oxidation resistance and thermal stability at high temperatures for long service life. The non-chlorinated additive package helps reduce environmental impact in case of leaks or stray mist, and facilitates waste oil disposal.

Applications

- Pneumatic equipment such as drifters, jackhammers, pavement breakers, rock drills and stoppers

Features/Benefits

- Non-chlorinated additive package for reduced environmental impact
- Excellent extreme-pressure properties
- Protects against wear and seizure
- Good adhesiveness to metal surfaces in the presence of moisture
- Good oxidation resistance and thermal stability
- Protects against rust and corrosion
- Low odor
- Low fogging tendency
- Good foam resistance

**Ashless,
Non-Chlorinated,
Extreme-Pressure
Air Tool Lubricant**

Contact Information

**U.S. Customer
Service:
1-800-640-1956**

**Technical Hot Line:
1-800-255-9556**

**International
Customer Service:
+1-832-486-3363
+1-832-486-3870**

**E-mail address:
*conocolubricants@
conocophillips.com***

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Ecoterra® Rock Drill Fluid

Typical Properties

ISO Grade	320
Specific Gravity @ 60°F	0.890
Density, lbs/gal @ 60°F	7.42
Color, ASTM D1500	5.0
Flash Point (COC), °C (°F)	240 (464)
Pour Point, °C (°F)	-15 (5)
Viscosity,	
cSt @ 40°C	320
cSt @ 100°C	24.3
SUS @ 100°F	1,703
SUS @ 210°F	121
Viscosity Index	97
Foam Test, ASTM D892	Pass
Rust Test, ASTM D665 A	Pass
Timken OK Load, ASTM D2782, lb	50

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2009 ConocoPhillips Company. The ConocoPhillips logo, Conoco, and the Conoco logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.



CSB-09 3835271
03/09